




INSTRUCTION MANUAL

TAKU BATHROOM SINK FAUCET

SKU: 25-1272-XX

INSTALLATION MANUAL

Single Hole Bathroom Sink Faucet




Tools you will need













Step 1: Remove mounting hardware
Remove the mounting screen


Remove the mounting screws, mounting nut, and rubber & metal washer from the mounting pipe




Step 2: Faucet installation
For three-hole installation:
Install deck plate, base plate,
and silicone sealant (optional)
For single-hole installation:
Install base plate



Step 3: Install faucet body
Insert faucet body into hole in
countertop or deck plate
Pre-drilled hole size:
1-3/8" (min) – 1-1/2" (max)
Max countertop thickness:
1-3/8"




Step 4: Install mounting hardware Install mounting hardware from underneath the countertop to the faucet




Step 5: Secure mounting hardware

hardware
Adjust direction of faucet body so that handle is on right side of faucet. Tighten mounting nut and mounting screws with Phillips screwdriver until snug



Step 6: Flush angle valves
Open the angle valves for a few seconds to flush out any dirt or debris before installation.



Step 7: Connect waterlines Connect waterlines to angle stops. Tighten both ends of waterlines with a wrench until snug.



Step 8: Flush the body and check for leaks
Remove aerator from spout. Turn faucet on and let the water run for 60 seconds to flush any debris.
Check for leaks at the connections.

Retighed if necessary.

Care & Maintenance *To keep the product clean & shining, follow the steps below:

- 1. Rinse with clean water & dry with a soft cloth
- 2. Do not clean with soap, acid polish, abrasives, or harsh cleaners
- 3. Do not use cloth with a coarse surface
- 4. Unscrew the aerator and clean when necessary



Thank You for Choosing FORM+

For additional support, please visit our website.

www.formplusdesign.com